



Dome E2c
Diagnostic-quality.
DICOM calibrated.

FEATURES:

- > High-bright color
- > Open architecture design
- > Automatic DICOM calibration
- > 21.3-inch screen
- > 500 cd/m² luminance
- > 600:1 contrast ratio

The Dome E2c is ideal for diagnostic viewing in PACS workstations, modality review, and multi-specialty clinical such as surgical OR, ER and ICU. The Dome E2c's highbright backlight technology and offers completely automatic and continuous DICOM conformance. With the flexibility of color and DICOM calibrated grayscale, the affordable Dome E2c eliminates the need to switch displays by providing the ability to perform multi-modality studies, fusion studies and 3-D rendered image readings on the same panel.



> Supported by Dome CXtra Software to ensure DICOM conformance



> Enhances visualization of 2-D color images, fusion images and 3-D reconstruction images



*All Dome EX displays come with Dome CXtra software. Dome Dashboard Software available as an option.

Medical Visualization Technologies



SPECIFICATIONS:	
LCD DISPLAY	
Technology	TFT AMLCD SPVA, 3 subpixels per pixel
Screen Size (diagonal)	21.3-inch (541.02 mm)
Display Resolution (pixels)	1200 x 1600 portrait, 1600 x 1200 landscape
Pixel Pitch	270µm, 94 dpi
Viewing Angle (CR 10:1)	± 85° (170°) horizontal and vertical
Response Time	16/16 ms typical
Optical Characteristics	
Brightness	Typical: 600 cd/m ² Default Calibrated: 500 cd/m ²
Contrast Ratio	600:1 typical
Palette	1786 unique shades of gray
DICOM Calibration	Calibration continually verified by Dome Cxtra™
Panel Interface/Connectivity	
Digital Video Input	DVI Revision 1.0 single data connector
Analog Video Input	VGA, S-Video, composite
Digital Communication & ID	DDC2B+EDID
USB Interface	Built-in USB1.1 Hub, One upstream port, two downstream ports
Video Input Formats	
Landscape Orientation	1600 x 1200, 24-bit color per pixel
Portrait Orientation	1200 x 1600, 24-bit color per pixel
VGA to XGA/SXGA	640 x 480 to 1024 x 768, 1280 x 1024 displayed in portrait and landscape
Calibration	
Technique	LCD panel individually characterized and calibrated at factory, DICOM calibration verification performed via RightLight™ (internal photometer) and Dome CXtra
Test Standards	AAPM TG18 Report No. 03, DIN 6868-57:2000
Calibration Type	DICOM Grayscale
Imaging/Graphics Controller	
Compatible Controller Support	AX4, NX1500
Physical Characteristics	
Display Size (without stand)	19" H x 14.75" W x 4" D (482.6mm x 374.65mm x 102mm)
Weight (without stand)	Less than 12 lbs (5.44 kg)
Mounting Options	Compatible with 100 mm VESA-compliant mounting standards, desktop stand
Power Requirements	
Power Input	100 to 240 VAC, Frequency of 50-60 Hz single phase, Less than 120 watts (typical)
Environmental	
Operating Temperature Range	10 to 35 degrees C
Certifications	
Medical	FDA 510(k)
Safety & Emission	CSA, EN60601-1, FCC, CE, CCC, TUV-GM, VCCI, C-Tick
Service and Support	
Warranty	5-year standard warranty

(Specifications may vary based on specific customized solution requirements.)

North American Corporate Offices

5750 Hellyer Avenue
San Jose, CA 95138
USA
Tel: 408.776.0085
Email: info@ndssi.com

U.S. East Coast Office

Dome Products
400 Fifth Avenue
Waltham, MA 02451
Phone: -781-895-1155
Fax: 781-895-1133
Email: info@ndssi.com

European Offices

Nijverheidscentrum 28
2761 JP Zevenhuizen (ZH)
The Netherlands
Tel: 31 180 63 43 56
Email: info@ndssi.nl

Asia Pacific Offices

1st Fl., RISE Building,
5-13, Asakusabashi 5-Chome,
Taito-Ku, Tokyo, Japan, 111-0053
Tel: 81 3 6420 3031
Email: info@ndssi.jp

© 2008, NDS Surgical Imaging.
Products may not be available in all markets and are subject to the regulatory or medical practices that govern individual markets. Always refer to the package insert, product label and/or user instructions before using any NDSSI product. Contact your NDSSI representative for more information. Products referenced with ™ designation are trademarks of NDSSI. Products referenced with ® designation are registered trademarks of NDSSI.

